

Data Sheet

Barracuda® 7200.12

The industry's leading combination of capacity, performance and reliability

**1 TB, 750 GB, 500 GB, 320 GB, 250 GB, 160 GB •
7200 RPM • SATA 3Gb/s with NCQ**

Key Advantages

- Sustainable technology for a green world:
 - Typically 70 percent or more of the materials used to build the drive is recycled.
 - Complies with the RoHS directive and several non-regulatory restrictions.
- 12th generation of the world's most popular desktop hard drive
- Ships with the most reliable and proven perpendicular magnetic recording technology
- Delivers high performance:
 - 125-MB/s maximum sustained data rate
 - Up to 3-Gb/s instantaneous burst
 - 32-MB cache on 1-TB and 750-GB drives, 16-MB cache on 500-GB and 320-GB drives, 8-MB cache on 250-GB and 160-GB drives

Best-Fit Applications

- Workstations
- Desktop RAID
- Gamer PCs
- High-end PCs
- Mainstream PCs
- USB/FireWire/eSATA personal external storage



Barracuda® 7200.12

The industry's leading combination of capacity, performance and reliability



Specifications	1 TB ¹	750 GB ¹	500 GB ¹	320 GB ¹	250 GB ¹	160 GB ¹
Model Number	ST31000528AS	ST3750528AS	ST3500418AS ST3500410AS	ST3320418AS	ST3250318AS	ST3160318AS
Interface Options	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ
Performance						
Transfer Rate, Max Ext (MB/s)	300	300	300	300	300	300
Sustained Data Rate OD (MB/s)	125	125	125	125	125	125
Cache (MB)	32	32	16	16	8	8
Average Latency (ms)	4.17	4.17	4.17	4.17	4.17	4.17
Spindle Speed (RPM)	7200	7200	7200	7200	7200	7200
Configuration/Organization						
Bytes per Sector	512	512	512	512	512	512
Reliability/Data Integrity						
Contact Start-Stops	50,000	50,000	50,000	50,000	50,000	50,000
Nonrecoverable Read Errors per Bits Read	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Annualized Failure Rate	0.34%	0.34%	0.34%	0.34%	0.34%	0.34%
Power Management						
Startup Current +12V Peak (A, ±10%)	2.0	2.0	2.0	2.0	2.0	2.0
Operating, Average (W)	<9.4	<9.4	<8.0	<8.0	<8.0	<8.0
Idle, Average (W)	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0
Environmental						
Temperature (°C)						
Operating	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Nonoperating	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock (Gs)						
Operating: 2 ms	70	70	70	70	70	70
Nonoperating: 1 ms	300	300	350	350	350	350
Acoustics (bels – sound power)						
Idle	2.5	2.5	2.6	2.6	2.6	2.6
Seek	2.7	2.7	2.75	2.75	2.75	2.75
Physical						
Height (in/mm)	1.02/26.1	1.02/26.1	0.78/20	0.78/20	0.78/20	0.78/20
Width (in/mm)	4.00/101.6	4.00/101.6	4.00/101.6	4.00/101.6	4.00/101.6	4.00/101.6
Depth (in/mm)	5.787/146.99	5.787/146.99	5.787/146.99	5.787/146.99	5.787/146.99	5.787/146.99
Weight (lb/kg)	1.4/0.64	1.4/0.64	1.2/0.54	1.2/0.54	1.2/0.54	1.2/0.54

¹ One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to hard drive capacity.

The Eco-Friendly Choice

The Seagate® Barracuda® 7200.12 drive delivers power savings without sacrificing performance. Customers can manufacture eco-friendly PC and external storage systems that meet energy-savings requirements.

The drive combines proven technology with expert manufacturing to deliver up to 1 TB of desktop storage. Customers can have the best of both worlds—top hard-drive performance and a high-capacity drive with a very small eco-footprint. Seagate minimizes the impact of our products and operations on the environment with

efficiency measures, such as replacing or renovating less-efficient equipment, resulting in a 20 percent increase in production efficiency on a per-hard-drive basis. This delivered a 158.93 million kWh savings in six months, or enough energy to power nearly 15,000 U.S. homes for one year. Seagate also has deployed aggressive waste minimization and recycling programs in facilities worldwide.

The Barracuda product family complies with the RoHS directive on hazardous materials.

www.seagate.com
1-800-SEAGATE (1-800-732-4283)

AMERICAS Seagate Technology LLC 920 Disc Drive, Scotts Valley, California 95066, United States, 831-438-6550
ASIA/PACIFIC Seagate Technology International Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 130-136, rue de Silly, 92773, Boulogne-Billancourt Cedex, France 33 1-4186 10 00

Copyright © 2009 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Barracuda, G-Force Protection and SoftSonic are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to hard drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Seagate reserves the right to change, without notice, product offerings or specifications. DS1668.5-0905US, May 2009