



Palit GTX 560 Ti SONIC

- **Embargo date: 2011.01.25, 6:00AM PST**
- **Palit Own Design GTX 560 Ti**
- **Sonic Overclocking Version**
 - **9% higher than non-OCed**
- **Compact size**
- **Dual-Fan thermal solution**



Product Photo

Product Name GTX 560 Ti Sonic	VGA Chip GTX 560 Ti	PN NE5X56TS1102-1140F	Core Name GF114
---	-------------------------------	---------------------------------	---------------------------

Specifications

Process technology	40nm
Processor Cores	384cores
Memory Amount	1024MB
Memory Interface	256bit
DRAM Type	GDDR5
Graphics Clock	900MHz
Memory Clock	2100MHz (DDR 4200MHz)
Processor Clock	1800MHz
Memory Bandwidth	134.4 (GB/Sec)
Power Consumption	180W

Output Support

Dual Dual-link DVI-I, HDMI, VGA



Accessory

Driver CD



Manual



Power Cable



Key Features

- Microsoft DirectX11 support
- NVIDIA CUDA technology with CUDA C/C++
- DirectCompute 5.0 and OpenCL support
- NVIDIA PhysX technology
- NVIDIA SLI Ready
- NVIDIA 3D Vision Surround Ready*
- NVIDIA PureVideo HD technology
- PCI Express 2.0 support
- Two dual-link DVI-I connectors
- One HDMI 1.4a connector
- Dual-link HDCP capable
- OpenGL 4.1 support



* Require NVIDIA SLI configuration, 3D Vision Glasses and 3pcs 3D Vision ready displays.

Minimum system requirements

Graphics card require:

- PCI Express or PCI Express 2.0-compliant motherboard with one dual-width x16 graphics slot
- Two 6-pin PCI Express supplementary power connector
- Minimum 500W or greater system power supply (with a minimum 12V current rating of 30A)
- Supported Operating Systems: Windows 7, Windows Vista, Windows XP

Dimension

PCB: 188mm(L) x 112mm(W)
Cooler :2 slot
Bracket: 2 slot

Retail Pack: 20 pcs per carton
Bulk Pack: 20 pcs per carton