

Palit GeForce GTX 660 Ti

- Embargo time: Aug 16th, 2012, 6AM PDT
- Palit Own Design GTX 660Ti
- 2 slot cooler
- Kepler Architecture
- DrMOS : Better Power Efficiency
- Better Overclocking Performance
- 3 Way SLI ready
- 28nm - high performance and low power
- Support for 4 concurrent displays
- Better cooler design, lower acoustic level



Specifications

VGA Chip	GeForce GTX 660 Ti
PN	NE5X66T01049-1043F
Core Name	GK104
Process technology	28nm
Processor Cores	1344 cores
Memory Amount	2048 MB
Memory Interface	192 bit
DRAM Type	GDDR5
Base Clock	915MHz
Boost Clock	980MHz
Memory Clock	3004MHz (DDR 6008MHz)
Memory Bandwidth	144.2(GB/Sec)
Power Consumption	150 W

Output Support

HDMI/DisplayPort/Dual DVI



Accessory

Driver CD Manual Power Cable



Key Features



- Kepler Architecture
- NVIDIA GPU Boost
- NVIDIA Adaptive Vertical Sync
- NVIDIA Surround
- Support for four concurrent displays
- NVIDIA DirectX 11 with DirectCompute 5.0 support
- NVIDIA PhysX technology
- NVIDIA 3 Way-SLI Ready
- NVIDIA 3D Vision Surround Ready
- NVIDIA CUDA technology
- PCI Express 3.0 support
- OpenGL 4.2 support
- OpenCL support



© 2012 NVIDIA Corporation. NVIDIA, the NVIDIA logo, and GeForce are registered trademarks of NVIDIA Corporation in the U.S. and other countries. All rights reserved.

Minimum system requirements

Graphics card require:

- PCI Express-compliant motherboard with one dual-width x16 graphics slot
- Two 6-pin PCI Express supplementary power connectors
- Minimum 450W or greater system power supply (with a minimum 12V current rating of 24A)
- Supported Operating Systems: Windows 7, Windows Vista, Windows XP

Dimension

PCB: 247mm(L) x 112mm(W)
Cooler : 2 slot
Bracket: 2 slot

Box: 400x270x72mm
Retail Pack: 10 pcs per carton